

ТРИФАЗНИ СУХИ МОТОРИ ЗА ХИДРАВЛИЧНИ СТАНЦИИ
 THREE-PHASE DRY MOTORS FOR HYDRAULIC STATIONS
 DREHSTROM DRY MOTOREN FÜR HYDRAULISCHE STATIONEN

ТИП TYPE TYP	Режим на работа Duty Cycle Betriebsart	Мощност Rated output		Номинални данни Parameters at Rated Output						Пускови характеристики Starting characteristics			Маца Weight	
		Bemessungs-leistung		Betriebswerte bei Bemessungsleistung						Viefaches des Bemessung			Gewicht	
		P _N		n _{N,50Hz}	n _{N,60Hz}	I _N		η	cosφ	I _s /I _N	M _s /M _N	M _{MAX} /M _N	G	
		kW	HP	min ⁻¹	min ⁻¹	220 A	380 A	%	-	-	-	-	kg	
2p=2											3000min ⁻¹			
AT 90 S2HYD	S1	1.50	2.00	2800	3350	6.4	3.7	77	0.80	6,0	2,2	2.6	12.0	
	S3-40%	2.20	3,00	2850	3410	9.5	5.5	77	0.79	4.0	1.5	1.8		
AT 90 L2HYD	S1	2.20	3,00	2850	3410	9.0	5.2	81	0.79	6,8	2,3	2.7	14.0	
	S3-40%	3.00	4.00	2850	3410	12.3	7.1	81	0.79	5.0	1.7	1.9		
AT 90 LB2HYD	S1	3.00	4,00	2880	3450	11.7	6.8	83	0.81	6,5	2,3	2.8	15.5	
	S3-40%	4.00	5.50	2880	3450	15.6	9.1	83	0.81	5.0	1.7	1.9		
2p=4											1500min ⁻¹			
AT 90 S4HYD	S1	1.10	1.50	1400	1670	5.4	3.1	72	0.75	4,3	2.2	2.6	12.0	
	S3-40%	1.50	2,00	1400	1670	7.3	4.2	72	0.75	3.2	1.6	1.9		
AT 90 L4HYD	S1	1.50	2,00	1400	1670	6.7	3.9	76	0.77	4,6	2.2	2.6	14	
	S3-40%	2.20	3.00	1350	1610	9.9	5.7	76	0.77	4,6	1.5	1.8		
AT 90 LB4HYD	S1	2.20	3.00	1350	1610	9.9	5.7	76	0.77	4,6	2.1	2.3	15.2	
	S3-40%	3.00	3.47	1350	1610	13.5	7.8	76	0.77	4,6	1.5	1.7		