

ТРИФАЗНИ ДВУСКОРОСТНИ ЕЛЕКТРОДВИГАТЕЛИ THREE-PHASE 2-SPEED ELECTRIC MOTORS DREHSTROMMOTOREN 2 FACH POLUMSCHALTBAR				СЕРИЯ SERIES REIHE	АТ	ТЕХНИЧЕСКИ ДАННИ TECHNICAL DATA TECHNISCHE DATEN BEI				50-60Hz		400V
ТИП TYPE TYP	Мощност output Bemessungs-leistung		Номинални данни at Rated Output Betriebswerte bei					Пускови характеристики Starting characteristics als Vielfaches des Bemessung			Мака Weight Gewicht	
	P <sub>N</sub>		П <sub>N50Hz</sub>	П <sub>N60Hz</sub>	I <sub>N</sub>	η	cosφ	I <sub>S</sub> /I <sub>N</sub>	M <sub>S</sub> /M <sub>N</sub>	M <sub>MAX</sub> /M <sub>N</sub>	M	
	kW	HP	min <sup>-1</sup>	min <sup>-1</sup>	A	%	-	-	-	-	kg	kg
Δ/Y		Схема на Даландер/ Dahlander Connection/ Dahlander Schaltung									750/1500 min <sup>-1</sup>	
AT 80 A8/4	0.18	0.24	670	804	0.8	51	0.63	2.5	2.0	2.1	13.5	8.0
	0.30	0.40	1320	1584	0.7	64	0.91	3.0	1.4	1.5		
AT 80 B8/4	0.25	0.33	670	804	1.1	53	0.63	3.0	2.1	2.2	15.2	9.1
	0.45	0.60	1280	1536	1.2	59	0.92	2.9	1.3	1.5		
AT 90 S8/4	0.40	0.55	630	756	1.4	58	0.69	3.0	1.9	1.9	18.5	14.0
	0.70	0.93	1200	1440	2.1	52	0.91	2.5	1.1	1.2		
AT 90 L8/4	0.55	0.75	630	756	2.0	59	0.68	3.0	1.9	1.9	21.3	15.2
	0.90	1.20	1260	1512	2.2	65	0.91	3.0	1.4	1.5		
AT 100 LK8/4	0.70	0.95	690	828	2.2	66	0.69	3.5	2.0	2.3	28.0	20.1
	1.10	1.50	1360	1632	2.4	72	0.91	4.0	1.4	1.8		
AT 100 L8/4	0.90	1.40	690	828	2.7	68	0.70	3.6	2.2	2.4	31.0	23.3
	1.50	2.20	1360	1632	3.2	73	0.92	4.0	1.4	1.8		
AT 112 M8/4	1.40	1.90	690	828	4.7	70	0.61	3.8	2.1	2.5	39.9	29.0
	2.20	3.00	1390	1668	4.7	78	0.86	4.9	1.8	2.4		
AT 132 S8/4	1.90	2.50	710	852	5.9	74	0.63	4.0	1.9	2.6	54.0	-
	2.70	3.60	1440	1728	5.4	81	0.90	5.6	1.4	2.4		
AT 132 MK8/4	2.40	3.20	710	852	7.5	75	0.62	4.0	1.9	2.6	79.0	-
	4.00	5.30	1430	1716	7.6	84	0.91	5.5	1.4	2.3		
AT 132 M8/4	3.00	4.00	720	864	9.1	78	0.61	3.8	1.5	2.5	89.0	-
	5.00	6.70	1430	1716	9.6	84	0.90	5.1	1.2	2.2		
AT 160 M8/4	5.00	6.70	720	864	17.4	77	0.54	3.7	1.7	2.9	95.0	-
	7.00	9.30	1450	1740	14.5	86	0.81	6.3	1.6	3.0		
AT 160 L8/4	7.00	9.30	720	864	22.4	78	0.58	3.6	1.5	2.6	110.0	-
	11.00	15.00	1440	1728	21.5	86	0.86	5.4	1.3	2.4		
Y/Y		Две отделни намотки/ Separate Windings/ Zwei Wicklungen									750/1000 min <sup>-1</sup>	
AT 80 A8/6	0.15	0.20	690	828	0.7	50	0.60	3.5	2.0	2.3	13.5	8.0
	0.18	0.25	930	1116	0.7	55	0.65	4.0	1.4	1.8		
AT 80 B8/6	0.18	0.25	690	828	0.8	52	0.61	3.6	2.2	2.4	15.2	9.1
	0.25	0.33	930	1116	1.0	54	0.66	4.0	1.4	1.8		
AT 90 S8/6	0.25	0.33	690	828	1.2	51	0.61	3.8	2.1	2.5	18.5	14.0
	0.37	0.50	930	1116	1.5	55	0.65	4.9	1.8	2.4		
AT 90 L8/6	0.37	0.50	710	852	1.6	53	0.63	4.0	1.9	2.6	21.3	15.2
	0.55	0.75	930	1116	2.2	54	0.66	5.6	1.4	2.4		
AT 100 LK8/6	0.55	0.75	690	828	1.7	66	0.69	3.5	2.0	2.3	28.0	20.1
	0.75	1.00	930	1116	2.5	68	0.65	4.0	1.4	1.8		
AT 100 L8/6	0.75	1.00	690	828	2.5	68	0.63	3.6	2.2	2.4	31.0	23.3
	1.10	1.50	930	1116	3.4	70	0.66	4.0	1.4	1.8		
AT 112 M8/6	1.10	1.50	690	828	3.7	70	0.62	3.8	2.1	2.5	39.9	29.0
	1.50	2.00	930	1116	4.6	72	0.65	4.9	1.8	2.4		
AT 132 S8/6	1.50	2.00	710	852	5.1	70	0.61	4.0	1.9	2.6	54.0	-
	2.20	3.00	930	1116	6.5	75	0.65	5.6	1.4	2.4		
AT 132 MK8/6	2.20	3.00	710	852	7.3	69	0.63	4.0	1.9	2.6	59.0	-
	3.00	4.00	930	1116	8.3	75	0.70	5.5	1.4	2.3		
AT 132 M8/6	3.00	4.00	720	864	9.2	68	0.69	3.8	1.5	2.5	79.0	-
	4.00	5.50	930	1116	11.5	72	0.70	5.1	1.2	2.2		
AT 160 M8/6	4.00	5.50	720	864	11.2	74	0.70	3.7	1.7	2.9	95.0	-
	5.50	7.50	930	1116	14.1	75	0.75	6.3	1.6	3.0		
AT 160 L8/6	5.50	7.50	720	864	15.8	70	0.72	3.6	1.5	2.6	110.0	-
	7.50	10.0	930	1116	18.5	75	0.78	5.4	1.3	2.4		