

ТРИФАЗНИ ЕЛЕКТРОДВИГАТЕЛИ THREE-PHASE ELECTRIC MOTORS DREHSTROMMOTOREN - СЕРИЯ АТА										50Hz 400V	
ТИП TYPE TYP	Мощност Rated output Bemessungsleistung		Номинални данни Parameters at Rated Output Betriebswerte bei Bemessungsleistung				Пускови характеристики Starting characteristics Anlaufverhalten			Маса IMB5	
	P_N		$n_{N,50Hz}$	I_N, A		η	$\cos\varphi$	I_s/I_N	M_s/M_N	M_{MAX}/M_N	Al
	kW	HP	min^{-1}	230	400	%	-	-	-	-	M kg
1500min⁻¹										2p=4	
ATA 63 A4	0.12	0.18	2760	0.8	0.4	55	0.71	4.0	2.1	2.4	3.7
ATA 63 B4	0.18	0.25	2760	1.0	0.6	60	0.73	4.0	2.1	2.4	4.1
ATA 63 C4	0.25	0.37	1400	1.1	0.6	67	0.84	4.0	2.1	2.4	4.4
ATA 71 A 4	0.25	0.34	1350	1.4	0.8	65	0.67	3.1	2.0	2.1	6.3
ATA 71 B 4	0.37	0.5	1360	1.9	1.1	68	0.72	3.3	2.0	2.1	7.0
ATA 80 A 4	0.55	0.75	1400	2.8	1.6	70	0.71	4.0	2.1	2.5	8.3
ATA 80 B 4	0.75	1.00	1400	3.6	2.1	72	0.72	4.3	2.5	2.8	9.4
ATA 90 S 4	1.10	1.50	1400	4.8	2.8	76	0.75	4.7	2.5	2.8	11.5
ATA 90 L 4	1.50	2.00	1400	6.4	3.7	76	0.77	4.6	2.6	2.9	13.5
ATA 90 LB4	2.20	3.00	1400	8.9	5.2	79	0.78	5.2	2.4	2.6	15.1
ATA 100 L4	3.00	4.00	1430	11.7	6.8	82	0.78	5.3	2.5	2.8	22.0
ATA 112 M4	4.00	5.50	1420	15.4	8.9	80	0.81	6.3	2.6	3.0	26.6
ATA 112 MB4	5.50	7.50	1410	20.5	11.8	83	0.81	6.9	2.6	3.0	30.2
ATA 132 S4	5.50	7.50	1430	19.7	11.4	85	0.82	6.5	2.2	2.9	40.5
ATA 132 M4	7.50	10.00	1450	27.6	16.0	86	0.79	7.0	2.2	2.9	50.0
ATA 132 MB4	11.00	15.00	1450	40.5	23.4	86	0.79	7.1	2.2	2.9	60.0