

ТРИФАЗНИ ЕЛЕКТРОДВИГАТЕЛИ THREE-PHASE ELECTRIC MOTORS DREHSTROMMOTOREN						ATF	100Hz	400V
ТИП TYPE TYP	Мощност Rated output Bemessungs-leistung		Номинални данни Parameters at Rated Output Betriebswerte bei Bemessungsleistung					Маса Weight Gewicht
	P _N		I _N	η	cosφ	M _N	η _{MAX}	M
	kW	HP	A	%	-	N.m	min ⁻¹	kg
2p=2						6000min-1		
ATF 71 A2	0.70	0.90	1.8	67	0.84	1.15	5820	6.3
ATF 71 B2	1.00	1.30	2.5	72	0.79	1.64	5820	7.0
ATF 80 A2	1.30	1.70	3.3	75	0.76	2.13	5820	8.3
ATF 80 B2	2.00	2.70	4.7	77	0.80	3.28	5820	9.4
ATF 80 C2	2.70	3.60	6.8	75	0.76	4.43	5820	10.0
ATF 80 D2	4.00	5.40	9.4	77	0.80	6.56	5820	11.8
ATF 90 S2	2.70	3.60	5.9	80	0.82	4.43	5820	11.5
ATF 90 L2	4.00	5.40	7.5	88	0.88	6.56	5820	13.5
ATF 90 LB2	5.50	7.40	11.8	83	0.81	9.02	5820	15.1
ATF 100 LK2	4.00	5.40	9.0	82	0.78	6.56	5820	18.7
ATF 100 L2	5.50	7.40	12.1	82	0.80	9.02	5820	22.0
ATF 100 LB2	7.20	9.70	14.9	83	0.84	11.81	5820	24.2